

Serial No. 09/913,708

**BEST AVAILABLE COPY****RECEIVED  
CENTRAL FAX CENTER****FEB 28 2007**LISTING OF THE CLAIMS

1. - 11. (cancelled)

5

12. (currently amended) Apparatus for reading a data stream, which comprises a multitude of raster points as reference points, the raster points specifying a raster, two adjacent raster points defining a segment, wherein the data stream comprises a plurality of sets of code words, a first set of code words being written in the first direction and a second set of code words being written in a second direction, the code words of the second set being assigned to segments of the data stream in accordance with a predetermined assignment rule, such that each code word of a set being assigned to a different segment, wherein a code word of the second set ~~may be~~ is distributed ~~divided up~~ over more than one segment in accordance with a predetermined rule, the apparatus comprising the following:

10

15

20

a first apparatus ~~device~~ for reading in a first direction of reading which corresponds to the first direction of writing;

a second device for reading in a second direction of reading which is opposite to the first direction of reading; and

25

a control device

for supplying the code words of the first set to the first reading device, each code word of the first set starting at the first raster point of a segment, and

30

**BLIT AVAILABLE COPY**

Serial No. 09/913,708

for supplying the code words of the second set to the second reading device, wherein one jumps to the second raster point of a segment in accordance with the predetermined assignment rule, and

5

wherein the control device is adapted for jumping at least to a further segment different from the segment, in which the part of the code word of the second set has been found, in accordance with the predetermined rule, after when all segments have been searched for code words of the second set in accordance with the predetermined assignment rule and at least only a part of the code word of the second set has been found in a segment and the one code word of the second set is still not present or not complete, one jumps at least to one further segment in accordance with the predetermined rule in order to and

10

15

wherein the control device is adapted for obtaining the at least one code word of the second set completely or a further part of the at least one code word of the second set from the further segment.

20

13. (cancelled)

14. (previously submitted) Apparatus as claimed in claim 12, wherein, if only one starting section of a code word is read by a writing device in one segment, this starting section is stored.

25

15 (previously submitted) Apparatus as claimed in claim 12, wherein the code words are Huffman code words.

30

16. (previously submitted) Apparatus as claimed in claim 12, wherein the code words represent information symbols and wherein code words of the first

## BEST AVAILABLE COPY

Serial No. 09/913,708

set represent more significant information symbols than code words of the second set or of further sets.

- 5 17. (original) Apparatus as claimed in claim 16, wherein the information symbols are spectral values of an audio signal, and wherein the code words of the first set are spectral values which are significant from a psycho-acoustic point of view and which are to be protected from error propagation due to a transmission error in the data stream.
- 10 18. (cancelled)
- 15 19. (currently amended) Method for reading a data stream which comprises a multitude of raster points as reference points, the raster points specifying a raster, two adjacent raster points defining a segment, in which method the data stream comprises a plurality of sets of code words, a first set of code words being written in the first direction and a second set of code words being written in a second direction, the code words of the second set being assigned to segments of the data stream in accordance with a predetermined assignment rule, such that each code word of a set is
- 20 assigned to a different segment, wherein a code word of the second set ~~may be divided up~~ is distributed over more than one segment in accordance with a predetermined regulation, the method comprising the following steps:
- 25 reading the code words of the first set, starting from a first raster point of a segment, in a first direction of reading which corresponds to the first direction of writing;
- 30 reading the code words of the second set, starting from a second raster point of a segment, in a second direction of reading which is opposite to the first direction of reading, wherein it is jumped, for reading the code

**BEST AVAILABLE COPY**

Serial No. 09/913,708

words of the second set, to the second raster point of a segment in accordance with the predetermined assignment rule, and

5        ~~wherein, after when~~ all segments have been searched for code words of the second set in accordance with the predetermined assignment rule and  
only a part of the code word of the second set has been found in a segment and ~~or at least the~~ a code word of the second set is not present ~~or still~~ not completely present, ~~one jumps jumping~~ to at least one further segment different from the segment, in which the part of the code word of  
10        the second set has been found, in accordance with the predetermined rule, and ~~so as to obtaining~~ the at least one code word of the second set completely or a part of the at least one code word from the further  
segment.